

P3D2-15

Power Handling

600 Watts RMS / 1200 Watts Max.

**Dual Voice Coil
Subwoofer 38 cm**

Technical Specifications

Impedance	Zn	2 x 2 Ohms
Voice Coil Diameter	Ø	64 mm
Voice Coil Winding Height		40,4 mm
Max. Linear Excursion	Xmax	+/- 15,2 mm
Max. Mechanical Excursion	Xmax (Peak)	+/- 28,6 mm
Cone Area	Sd	894 cm ²
Moving Mass	Mms	393,1 g
DC Resistance	Re	2 x 1,6 Ohms
Resonance Frequency	Fs	21,7 Hz
Mechanical Q-Factor	Qms	7,2
Electrical Q-Factor	Qes	0,58
Total Q-Factor	Qts	0,54
Equivalent Air Volume	VAS	155,8 L
VC Inductance	Le	4,1 mH
Flux Density	B/L	17,1 N/A
Efficiency 1W/1m	SPL	86 dB

Recommended Enclosure

Sealed Box	
Sealed Volume:	44,7 L
-3 dB Rolloff (F3):	38 Hz

Recommended Enclosure

Ported Box	
Vented Volume:	75,3 L
Port Diameter:	100 mm
Port Area:	80 cm ²
Port Length:	25 cm
Tuning Freq. (Fb):	32 Hz
-3 dB Rolloff (F3):	30 Hz

Mechanical Components

- Diecast Aluminium Basket
- Aluminium Cone
- Santoprene Surround
- Aluminium Dustcap
- Dual Spider
- Aluminium Voice Coil Former

Dimensions & Weight

External Diameter:	410 mm
Mounting Diameter:	353 mm
Mounting Depth:	193 mm
Shipping Weight:	11,4 kg

